

TEST REPORT

CLIENT:

Company:	ForeverLawn, Inc.	Report Number:	64672C
Address:	5801 Mayfair Road	Lab Test Number:	2736-4634
	North Canton, OH 44720	Test Date:	August 7, 2015
		Report Date:	September 4, 2015
		Page:	1 of 1
Requested By:	Robb Wolf		

TEST MATERIAL:

Material Type:	Knitted Monofilament with thatch Synthetic Turf					Date Received:		8/5/2015)
Material Condition:	EXCELLENT:	XXX	GOOD:		POOR:		REJE	CTED:	
Style:	K9Grass Classic								
Roll #:	80074212								

TESTING METHODS REQUESTED:

Testing Services Inc. was instructed by the client to test for the following				
Standard:	ASTM D5034	Test Method:	Standard Test Method for Breaking Strength of Textile Fabrics (Grab)	

SAMPLING PLAN:

Sampling Date: 8/5/2015

- Specimen sampling is performed in the sampling department at TSI beside the ground level dock door.
- The sampling size of specimens is determined by the test method requirements.
- In the event a specific sampling size is not called for, a determination will be made based on previous testing experience, and approved for use by an authorized manager.
- All samples are subjected to the outside environmental conditions of temperature and relative humidly.
- Sample requiring pre-determined exposure to specified environmental conditions based on a specific test method, take place in the departments in which they are tested

DEVIATION FROM TEST METHOD:

 DEVINATION FROM FEOT METHOD.							
State reason for any Deviation from, Additions to, or Exclusions From Test Method.							
None							

TEST SUMMARY:

ASTM D5034 Average Grab Tear Strength (Length Direction) 255.3 lbs/force ASTM D5034 Average Grab Tear Strength (Width Direction) 270.8 lbs/force	TEST METHOD	TEST DESCRIPTION	TEST RESULT
ASTM D5034 Average Grab Tear Strength (Width Direction) 270.8 lbs/force	ASTM D5034	Average Grab Tear Strength (Length Direction)	255.3 lbs/force
::::::::::::::::::::::::::::::::::::::	ASTM D5034	Average Grab Tear Strength (Width Direction)	270.8 lbs/force

Lengin									
Tear #1	254.0 lbs/force	Tear #2	243.6 lbs/force	Tear #3	262.1 lbs/force	Tear #4	256.2 lbs/force	Tear #5	260.5 lbs/force
Width									
Tear #1	268.5 lbs/force	Tear #2	240.3 lbs/force	Tear #3	271.0 lbs/force	Tear #4	294.8 lbs/force	Tear #5	279.2 lbs/force

Uncertainty:

We undertake all assignments for our clients on a best effort basis. Our findings and judgments are based on the information to us using the latest test methods available. TSI can only ensure the test results for the specific items tested.

Unless otherwise noted in the deviations sections of this report, all tests performed are in compliance with stated test method.

Test Report Approval:

Erle Miles, Jr. VP, Testing Services Inc

TSi Accreditation: Our laboratory is accredited by the US Dept of Commerce, National Institute of Standards and Technology: ISO/IEC 17025:2005. Our code # is: NVLAP 100108-0. TSi is a certified independent testing laboratory by the Synthetic Turf Council

Form:	Rev: Revision Date: Page 1 of 1				
Release Date:	Control Type: Electronic – Expires 24 hours after this date: Sep. 8, 15				
		Printed copies are uncontrolled			